HERRINGBONE · REF CFA097

Smoked Brushed & UV Lacquered Oak Herringbone

Smoked Brushed & UV Lacquered Oak Herringbone is a smoked oak with a deeper brown tone and natural colour movement. Brushing lifts the grain so the figure of the wood reads clearly and gives a subtle texture you can feel. The UV lacquer is cured in the factory, giving a durable, easy-clean surface that is ready to live on once laid.

Supplied 90 × 400 mm with a 3 mm wear layer on a 14 mm engineered board. Laid in the classic zig-zag, herringbone brings rhythm and craft to hallways, living rooms and open-plan kitchen-diners.

Product specification

Product name	Smoked Brushed & UV Lacquered Oak Herringbone
Reference code	CFA097
Flooring type	Engineered oak — herringbone
Construction	Engineered — oak wear layer bonded to a stable core
Overall thickness	14 mm
Wear layer thickness	3 mm
Board width	90 mm
Board length	400 mm
Wood species	Oak
Grade	*Available on request*
Surface finish	Smoked brushed & UV lacquered
Installation method	*Available on request*
Joint profile (T&G; / click)	*Available on request*
Underfloor heating	*Available on request*
Max. floor surface temperature	*Available on request*
Installation conditions	*Available on request*
Pack coverage	*Available on request*
Standards & certifications	*Available on request*

Notes

Items marked *available on request* are not yet confirmed for this product and are deliberately left blank — please contact us to confirm installation method, underfloor heating limits, pack coverage and certification before specifying or installing. Natural oak varies in colour and grain between boards and batches; photographs are representative, so always approve a physical sample before ordering.

Care: see the Cambridge Floors **Lacquered Oak Floors** care guide.